



1.95M cylinders direct drive carriers without chain, improving strength

50%, safer and reducing the risk of chain broken



Equipped with SHUNLI 'one side control two side unlock' device. Just pull the handle on one side and both posts will be unlocked. Safer and more easy to use.



Well-known brands aluminium alloy shell copper core motor, fast heat dissipation, high efficiency, long service life.



the EU test standard



Steel core wire rope Japanese / Italian oil seals



Hook type safety Prevent the slipping when slider worn.



The standard height extension



2 & 3 stages ultra-low arms, for the low chassis sport car, strength 20% higher



Solid steel plate



Safety lock through the EU test



16mm solid steel plate



Safety lock through the EU test

High strength solid steel arms & arm lock system which reach the EU standard

Product Features:

- ◆ Oil cylinder parts made by automatic high rotation speed CNC lathe ensure the excellent finish and concentricity
- ◆ Japanese oil sealing elements, overload protection, international brand oil pipe
- ◆ Direct drive twin cylinders, with safety steel wire as synchronization
- ◆ Polymer wear-resistance slider
- ◆ Single side safety control both side unlocked safety, arm locks with tooth type ratchet, multi-safety device, more reliable
- ◆ Gate type, for operation more easy, no obstruction onto the floor
- ◆ Roof protection safety device, automatic arm lock by built in ratchet tooth
- ◆ Shot blasting and high temperature baking powder coated surface finish

Model	Capacity	Min.Height	Lifting Height	Rise Time	Descending Time	Total Height	Inner Width	Total Width
UL-245L	4500kg	95mm	1990mm	50s	30s	3900mm	2860mm	3440mm

Motor power: 2.2KW Motor voltage: 415V, 3PH, 50HZ

